


BORNIT®



— ROCK SOLID CONNECTIONS



Asphalt Adhesive Sprayer


A strong tool for strong users

Road



www.bornit.com





Road

A strong tool for strong users

Asphalt Adhesive Sprayer

The BORNIT® Asphalt Adhesive Sprayer is the essential tool for precise and energy-saving application of bitumen emulsion C40 BF5-S (asphalt adhesive) on all types of small construction sites.



The well thought-out design scores with great ease of use and high utility value. The pressure tank has a usable capacity of 18 litres and can be completely emptied with one filling of compressed air. This results in a spraying capacity of up to 90 m² with one filling.

The practical 25 kg Asphalt Adhesive canister from BORNIT® and the range of accessories for use with truck compressed air or via car valve set no limits to the application range of the Asphalt Adhesive Sprayer.

- ① 600 mm stainless steel atomiser lance
- ② large filling opening
- ③ ergonomic handle
- ④ 5 m spiral hose with 360° rotatable coupling
- ⑤ pressure gauge
- ⑥ overpressure safety valve
- ⑦ compressed air connection
- ⑧ smooth-running castors

BORNIT® Asphalt Adhesive C40BF5-S

cationic bitumen emulsion, binder content approx. 40 %, for pre-spraying soiled and aged asphalt surfaces, pre-treatment before application of mix or cation-active bitumen emulsions, quality according to TL BE-StB 15

accessories for BORNIT® Asphalt Adhesive Sprayer:

- car valve adapter
- truck valve adapter with hose (2 m)
- fan nozzles
- replacement spiral hose (5 m)

System products:

BORNIT® Asphalt Adhesive R2 C40BF5-S
BORNIT® Asphalt Adhesive Sprayer
BORNIT®-MultiClean
BORNIT® MultiClean Spray
BORNIT® Bitumen Cleaner



Type	Content	Colour	sufficient for	Order-No.	EAN-Code	Palletisation
	190 kg	black	approx. 422.2 - 950.0 m ²	6900002540	4 017228 00712 0	190 kg
	1000 kg	black	approx. 2222.2 - 5000.0 m ²	6900003290	4 017228 00694 9	1000 kg

A strong tool needs strong properties:

- high-quality working results due to optimal asphalt adhesive application
- precise and comfortable working
- stable and manoeuvrable construction
- simple and ergonomic handling
- practical accessories



Technical features:

Design:	small sprayer with stainless steel plastic atomiser lance
Compressed air connection:	KSG 1/4" NW7
Usable capacity:	18 ltr.
Tank size:	24 ltr.

Operating temperature:	max. +40 °C
Operating pressure:	6-8 bar
Empty weight:	approx. 11 kg
Dimensions (LxWxH):	330 x 780 x 280 mm

BORNIT®



— ROCK SOLID CONNECTIONS



Your dealer:

BORNIT-Werk Aschenborn GmbH

Your partner for building and road construction products!
Reichenbacher Straße 117 | 08056 Zwickau | Germany

Phone: +49 375 27 95 - 0
Fax: +49 375 27 95 - 150
E-Mail: info@bornit.com
Web: www.bornit.com



www.bornit.com

